

Non-Cobrahead LED Fixtures



City of Los Angeles
Department of Public Works
Bureau of Street Lighting



Bold is the latest approved from each manufacturer

These products have been tested and approved by the Energy Efficiency Division. This chart will be updated as new technology becomes available. It is recommended that designers use the lowest wattage that meets lighting criteria. Italicized numbers are aesthetic options and are optional. Locked .ies files should be used for final design purposes.

***LARGER AND SMALLER SIZES AVAILABLE, DESIGNER SHOULD DETERMINE WHAT SIZE/COLOR IS APPROPRIATE FOR PARTICULAR DESIGN**
**** SEE IES FOLDER FOR APPROVED DRAWING**

| | Approved Luminaires | Catalog Number | Power | Lumens |
|-----------------------------------|-------------------------------------|---|--------------------|---------------------|
| ACORNS | Lumec Serenade | S56-010-xxWxxLED3K-R-GL-LE3-120-SFX-CHR-FN10-SCZS211G20SM Approved Size Variants: 35W32LED, 55W48LED, 80W48LED | 36 W 55 W, 79 W | 3,439 5064, 7132 |
| | Sternberg Old Town Acorn* | A850SRLED-ROAM/BD4PT /6ARC30T3 /MDL03 /BLK | 96 W | 7,630 |
| LANTERNS | Lumec Octagonal Lantern (L70)* | L70-003-40W49LED3K-ES -GL -FC -LE3-120-SF70 -CHR-HK16 -SC-014 | 47 W | 4,600 |
| | Lumec Square Lantern (S41)* | S41-001-35W32LED3K-R-ACDR-C-LE3-120-SF41 -CHR-SCZS211G20SM | 35 W | 2,620 |
| | Lumec Ancestra Lantern (AT30)* | AT30-55W48LED3K-R-LE3A | 55 W | 5,648 |
| | King Octagonal Lantern (K56)* | CLA-K56-S -T-P4AR-III-100(SSL)-7030-120:277 - 3K | 91W | 9,522 |
| PENDANTS | Lumec Renaissance (RN20)* | RN20-80W48LED3K-ACDR-LE3R-120-SMA | 79 W | 7,863 |
| | King Pendant (K803)* | CLA-K803-P4RAD-III-60(SSL)-8060-120:277-KPL20 -PR7-3K | 60 W | 5,903 |
| | King Pendant (K809)* | CLA-K809-P4SA-III-120(SSL)-8060-120:277V-KPL20 -PR7-3K | 120 W | 10,770 |
| | ANP Tokyo Special | SCL-ANP-WG024-FP-103-LD3-N-T3-30K | 103 W | 9,251 |
| SECURITY | Holophane Pedestrian LED | MSPL2P1030KASSA 5RL03 (<i>Color and Skirt optional</i>) | 27W | 3,451 |
| | King Coachman* | CLA-K204-P4GS-III-25w/40w/60w/75w (SSL)-7030-HE7-3000K-120;277-KPL10 SPRING STREET GREEN ** | 25 W | 2,942 |
| | King Coachman Retrofit | KCK200-P4SH-III-25W(SSL)-7030-120:277V-EE4-3000K-KPL10-SPRING STREET GREEN | 25 W | 2,370 |
| | Gardco Form 10 Retrofit * | S//RKL-MA17L-2-20LA-WW-UNIV (3000K) | 20 W | 1,800 |
| | Cree Edge Round * | ARE-EDR-2S-R5- 04-E-UL-BK- 175-30K | 17.5 W | 2,400 |
| | Cree Edge Square * | ARE-EDG-2S-DA- 04-E-UL-BK- 175-30K | 17.5 W | 2,400 |
| | Lumec Domus * | DOS-007-40W30LED3K-002-ES-LE3F-UNIV-CHR-DMG-PRMA-SCZS211G20SM | 20 W | 1,483 |
| Leotek GreenCobra Jr0 15H @ 300mA | GCJ0-15H-MV-WW-2R-GY-300-PCR7 | 15 W | 1,810 | |
| SOFFIT | Dialight * | LBW1N1A (3000K) | 45 W | 3,800 |
| | Lumec * | [RETRO-479]-65W42LED3K-R-LE5F-120-[FAWS-012]-BKTX | 45 W | 4,173 |
| | King * | CLA-P4FL-V-25(SSL)-7030-3K | 25 W | 3,047 |
| SCREW- IN LAMP | Truly Green Solutions | 310826-G4-300 (2600K NO UP-LIGHT) | 36W | 5,580 |
| | Truly Green Solutions DS (Dark Sky) | 318036-26-D-C-E39 (<i>Down Lighting Shield - No Up Light</i>) | 36W | 3,900 |
| | Philips | 40ED28/LED/727/ND 120-277V (2600K) | 40 W | 5,000 |
| RETROFIT KIT | Cree | DPTASBFRA26K-ULUF | 34 W | 3,575 |
| | Eye Lighting | LEW-37WH-433-830-HWD-UN01-UNV UNIVERSAL (2600K) | 37 W | 2,959 |
| | Amerlux | RF AVI-U-SO-3L/LA CITY (2600K) | 41 W | 2,830 |
| | Amerlux | RF AVI-U-T14-SO-3H/LA CITY (3000K) | 60 W | 4,990 |